



SPP-125

Order No.: 10.1070

Price upon request

PRODUCTINFOS

Midrange speaker, 22 W, 8 Ω

Closed basket, no further midrange cabinet required.

This series of speakers with polypropylene cone is very well-suited for replacing defective 8 Ω speakers in hifi speaker systems.

TECHNICAL SPECIFICATIONS

SPP-125

Impedance (Z) 8 Ω

Frequency range 800-8,000 Hz

Resonant frequency (fs) 550 Hz
Power rating 22 W
Peak music power output 45 W

Sensitivity 92 dB/W/m



SPP-125

Hole spacing Y-axis

Type of speaker

DC resistance (Re) 6.5 Ω Voice coil induct. (Le) 0.2 mH Voice coil diameter Ø 20 mm Voice coil former aluminium Eff. cone area (Sd) 73 cm^2 Magnet weight 150 g Magnet diameter Ø 70 mm Mounting cutout Ø 110 mm Mounting depth 43 mm Mounting hole diameter Ø 122 mm Hole spacing X-axis 86 mm

Dimensions Ø 131 mm x 50 mm

86 mm

5"

Outside diameter Ø 131 mm

Width Ø 131 mm

Depth 50 mm

Admiss. ambient temp. 0-40 °C

Weight 0.472 kg

Sales unit 1

dB Ω 90

SPP-125(10.1070)



